



By Appointment to
Her Majesty the Queen
Manufacturers of Access Equipment
Clow Group Ltd., Glasgow



Clow Group Ltd

Ladder Inspection Information

Leaning Ladders

Ladder Safety Check Sheet (Maintenance, Repair and Storage)



ISO 9001:2008
Q05618





Ladder Inspection Information

LADDER SAFETY CHECK SHEET (MAINTENANCE, REPAIR AND STORAGE)

Single and Multi-Section Leaning Ladders

Maintenance checks before use:

Check that the stiles, (uprights), are not bent, bowed, twisted, dented, cracked, corroded, or rotten.

Check that the stiles around the fixing points for other components are in good condition.

Check that fixings, (usually rivets, screws or bolts), are not missing, loose or corroded.

Check that rungs and any corner braces are not missing, loose, excessively worn, corroded or damaged.

Check that the rung hooks are not missing, damaged, loose or corroded and engage properly on the mating stile.

Check that feet/end caps are not missing, loose, corroded or damaged.

Check that the entire ladder is free from contaminations, (e.g. dirt, mud, paint, oil or grease).

Check that locking catches, (if fitted), are not damaged or corroded and function correctly.

IMPORTANT: If any of the above checks cannot be satisfied you should NOT use the ladder.



Ladder Inspection Information

LADDER SAFETY CHECK SHEET (MAINTENANCE, REPAIR AND STORAGE)

Single and Multi-Section Leaning Ladders

Repairs:

You should **NOT** attempt to repair the ladder unless you are qualified to do so. You can seek advice from the manufacturer regarding repair or replacement.

Storage:

The important consideration when storing a ladder should indicate the following:

Is the ladder stored away from areas where its condition could deteriorate more rapidly, (e.g. dampness, excessive heat or exposed to the elements)?

Is the ladder stored in a position which helps its to remain straight, (e.g. Hung by the stiles on proper ladder brackets or laid on a flat clutter free surface)?

Is the ladder stored where it cannot be damaged by vehicles, heavy objects, or contaminants?

Is the ladder stored where it cannot cause a trip hazard or an obstruction?

Is the ladder stored securely where it cannot be easily used for criminal purposes? If the ladder is permanently positioned, (e.g. on scaffolding), is it secured against unauthorised climbing, (e.g. by children)?



Clow Group Ltd

**Clow Group Ltd. (London)
Diamond Ladder Factory
562-584 Lea Bridge Road
London
E10 7DN
Tel: 0208 558 0300
Fax. 0208 558 0301**

**Clow Group Ltd. (Midlands)
Clow Business Park
Garratts Lane
Cradley Heath
B64 5AW
Tel. 0121 559 5222
Fax. 0121 559 0330**

**Clow Group Ltd. (Belfast)
2/24 Limestone Road
Belfast
BT15 3AJ
Tel. 02890 749748
Fax. 02890 749758**

**Clow Group Ltd. (Glasgow)
185 Broad Street
Glasgow
G40 2QR
Tel. 0141 554 6272
Fax. 0141 551 0813**

**enquiries@clowgroup.co.uk
www.clowgroup.co.uk**